

HG

Professional Standard of the People's Republic of China

HG/T 20611-2009

Replace HG 20611-1997

钢制管法兰用具有覆盖层的齿形组合垫 (PN 系列)

Covered Serrated Metal Gaskets for Use with Steel Pipe Flanges

(PN Designated)

Issued on Feb 05, 2009

Implemented on Jul 01, 2009

**Issued by the Ministry of Industry and Information Technology of the People's Republic of
China**

Covered Serrated Metal Gaskets for Use with Steel Pipe Flanges

(PN Designated)

1. Scope

This Standard specifies the type, dimension, technical requirements and mark for steel pipe flanges (PN designated) with covered serrated metal gaskets.

This standard applies to serrated compound gaskets with envelop layers used for steel pipe flange with PN ranging from PN16 to PN160, as shown in HG/T 20592.

2. Normative References

The articles contained in the following documents have become this standard when they are quoted herein. For the dated documents so quoted, all the modifications (excluding corrections) or revisions made thereafter shall not be applicable to this Standard. For the undated documents so quoted, the latest editions shall be applicable to this Standard.

“Hot-rolled sheets and strips of carbon structural steels and high strength low alloy structural steels” GB/T 912

“Hot rolled stainless steel plate sheet and strip” GB/T 4237

“Cold Rolled Stainless Steel Plate Sheet and Strip” GB/T 3280

“Steel Pipe Flanges (PN designated)” HG/T 20592

“Specification for selection of Steel Pipe Flanges, Gaskets and Bolting (PN designated)” HG/T 20614

“Specifications of Flexible Graphite Sheets” JB/T 7758.2




“Polytetrafluoroethylene sheet” QB/T 3625

3. General Specification

3.1 Types and Codes

The type, code, section form of the gasket and its types applied to the seal face of flanges shall conform to regulations in Table 3.0.1.

Table 3.1 Typical type codes of gaskets

Type	Code	Section form	Applicable flange sealing face types
Basic type	A		TF/GF or FF/MF
The whole belt to the middle ring	B		RF ^a
Flexible belt to the middle ring	C		RF ^a

As well as applied to the wholly plane reverse seal of the flange.

3.2 The Pressure nominal and dimension

3.2.1 The applicable PN for gaskets is as: PN16, PN25, PN40, PN63, PN100, PN160.

3.2.2 The dimensional range of DN applicable to this standard could refer to Table 4-1 and 4-2.

3.3 Application of gaskets

3.3.1 Working temperature range shall be in accordance with Table 3.3.1.

3.3.2. The type and materials for gaskets shall be selected according to fluid, operating conditions, materials, and seal type of flanges, superficial roughness and bolt loads. Gaskets used for particular purposes shall get confirmed by supplier.

3.3.3 The selecting of gaskets, flanges and bolting shall conform to regulations of HG/T 20614.

Table 3.3.1 Working temperature range of gaskets

Covered serrated metal gasket		Cover materials		Working temperature range (°C)
Designation	Standard	Name	References	
0Cr18Ni9 (304)	GB/T 4237 GB/T 3280	Flexible graphite	JB/T 7758.2	-200~+650 ^a
00Cr19Ni10 (304 L)		PTFE	QB/T 3625	-200~+200
0Cr17Ni12Mo2 (316)				
00Cr17Ni14Mo2 (316 L)				
0Cr18Ni10Ti (321)				
0Cr18Ni11Nb (347)				
0Cr25Ni20 (310)				

If used as the oxidant, the maximum working temperature shall be 450°C.

完整版本请在线下单

或咨询：

TEL： 400-678-1309

QQ： 19315219

Email：info@lancarver.com

<http://www.lancarver.com>

对公账户：

单位名称：北京文心雕语翻译有限公司

开户行：中国工商银行北京清河镇支行

账 号：0200 1486 0900 0006 131

支付宝账户：info@lancarver.com

注：付款成功后，请预留电邮，完整版本将在一个工作日内通过电子 PDF 或 Word 形式发送至您的预留邮箱，如需索取发票，下单成功后的三个工作日内安排开具并寄出，预祝合作愉快！